

無熔線斷路器 | NF系列

型名	額定電流(A)	啟斷容量 kA Icu/Ics 註1.				外型及安裝尺寸(mm)				牌價	
		220V	380V	440V	600V	a	b	c	ca		
NF400-CN	2P	250.300.350.400.	35/18	25/13	22/11	14/7	140	257	103	155	6,090
	3P						185				6,690
	4P						185				11,060
NF400-SN	2P	250.300.350.400.	50/25	35/18	30/15	20/10	140	257	103	155	7,480
	3P						185				7,800
	4P						185				11,630
NF400-HN	2P	250.300.350.400.	85/43	50/25	42/21	25/13	140	257	103	155	8,290
	3P						185				8,760
	4P						185				11,680
NF630-CN	3P	500.600.630.	35/18	25/13	22/11	14/7	210	275	103	155	13,120
	4P						280				16,000
NF630-SN	3P	500.600.630.	50/25	35/18	30/15	20/10	210	275	103	155	13,510
	4P						280				16,490
NF630-HN	3P	500.600.630.	85/43	50/25	50/25	25/13	210	275	103	155	14,650
	4P						280				16,700
NF800-CN	3P	700.800.	50/25	35/18	30/15	20/10	210	275	103	155	19,540
	4P						280				23,430
NF800-SN	3P	700.800.	85/43	50/25	50/25	25/13	210	275	103	155	20,060
	4P						280				23,810

註 1.表內之 Icu / Ics 皆為對稱值 (sym)。

無熔線斷路器 | NF系列 | 訂貨式生產

型名	額定電流(A)	啟斷容量 kA Icu/Ics 註1.				外型及安裝尺寸(mm)				牌價	
		220V	380V	440V	600V	a	b	c	ca		
NF50-SN	2P	10.15.20.30.40.50.	10/5	7.5/3.8	7.5/3.8	5/2.5	50	130	68	86	1,010
	3P						75				1,130
	4P						100				1,980
NF50-HN	2P	10.15.20.30.40.50.	25/13	15/7.5	10/5	5/2.5	50	130	68	86	1,030
	3P						75				1,180
	4P						100				2,060
NF100-MN	2P	10.15.20.30.40.50.	15/7.5	10/5	7.5/3.8	5/2.5	50	130	68	86	1,040
		60.75.100.					1,330				
	3P	10.15.20.30.40.50.					75				1,210
		60.75.100.					1,570				
	4P	10.15.20.30.40.50.					100				2,070
		60.75.100.					2,920				
NF100-HN	2P	10.15.20.30.40.50.60.75.100.	50/25	30/15	25/13	15/7.5	60	155	68	90	2,020
	3P						90				2,140
	4P						120				3,950
NF225-CN	2P	125.150.175.200.225.	30/15	22/11	15/7.5	7.5/3.8	105	165	68	92	2,900
	3P						140				3,400
	4P						140				5,360
NF225-SN	2P	125.150.175.200.225.	50/25	30/15	25/13	15/7.5	105	165	68	92	4,130
	3P						140				4,580
	4P						140				5,580

註 1.表內之 Icu / Ics 皆為對稱值 (sym)。

額定啟斷容量之「非對稱值」與「對稱值」數值對照表

非對稱值(asym)	15	18	20	22	25	30	35	40	50	60	75	100	120	150
對稱值(sym)	14	15	18	20	22	25	30	35	42	50	65	85	100	125