



## 無熔線斷路器 | BH系列

註 1. 『\*\*』表示為啟斷容量 a sym / sym 值。  
 2. BH、BHU 1P之機種，訂貨時請註明電壓值110V或220V。

型名	額定電流 (A)	啟斷容量 kA sym			外型及安裝尺寸 (mm)				牌價						
		110V	220V	380V	a	b	c	ca							
BH	1P	10.15.20.30.40.50.	5*	-	-	25	95	58.5	77.5	100					
		15.20.30.40.50.	-	5*						130					
		60.75.100.	5	-						195					
	2P	10.15.20.30.40.50.	-	5	-	50	95	58.5	77.5	220					
		60.75.100.	-	5						480					
	3P	10.15.20.30.40.50.	-	5	-	75	95	58.5	77.5	490					
60.75.100.		-	5	1,015											
BHU	1P	15.20.30.40.50.	10*	-	-	25	95	58.5	77.5	140					
		15.20.30.40.50.	-	10*						210					
	2P	15.20.30.40.50.	-	10	-	50	95	58.5	77.5	310					
		60.75.100.	-	10						660					
	3P	15.20.30.40.50.	-	10	-	75	95	58.5	77.5	680					
		60.75.100.	-	10						1,320					
BHH	1P	15.20.30.40.50.	15	10	-	25	95	58.5	77.5	225					
	2P	15.20.30.40.50.	-	15						10	50	95	58.5	77.5	465
		60.75.100.	-	15											1,030
	3P	15.20.30.40.50.	-	15						10	75	95	58.5	77.5	1,100
60.75.100.		-	15	1,690											
BHS	1P	15.20.30.40.50.	25/22**	-	-	25	95	58.5	77.5	340					
		15.20.30.40.50.	-	25/22**						680					
	2P	15.20.30.40.50.	-	25/22**	-	50	95	58.5	77.5	1,080					
		60.75.100.	-	25/22**						1,130					
	3P	15.20.30.40.50.	-	25/22**	-	75	95	58.5	77.5	1,710					
		60.75.100.	-	25/22**											

## 無熔線斷路器 | BH系列 | 插入式 | 訂貨式生產

型名	額定電流 (A)	啟斷容量 kA sym			外型及安裝尺寸 (mm)				牌價		
		110V	220V	380V	a	b	c	ca			
BPL	1P	15.20.30.40.50.	5	-	-	25	74	60.5	74	100	
	2P	15.20.30.40.50.	-	5						50	220
		60.75.100.	-			5					480
	3P	15.20.30.40.50.	-	5		-				75	74
60.75.100.		-	5	1,015							
BLU	1P	15.20.30.40.50.	10	-	-	25	74	60.5	74	140	
	2P	15.20.30.40.50.	-	10						50	310
	3P	15.20.30.40.50.	-	10		75					680
BLS	2P	60.75.100.	-	10	-	50	74	60.5	74	660	
	3P	60.75.100.	-	10						75	1,320
BAH	1P	15.20.30.40.50.	15	10	-	25	79	61	77.5	225	
	2P	15.20.30.40.50.	-	15						10	50
		60.75.100.	-			15					
	3P	15.20.30.40.50.	-	15		10				75	79
60.75.100.		-	15	1,690							