



## 無熔線斷路器 | NF系列

註 1.表內之 Icu / Ics 皆為對稱值 (sym)。

型名	額定電流 (A)	啟斷容量 kA Icu/Ics 註1.				外型及安裝尺寸 (mm)				牌價	
		220V	380V	440V	600V	a	b	c	ca		
NF30-SN	2P	3.5.10.15.20.30.	5/2.5	2.5/1.3	2.5/1.3	1.5/0.8	50	130	68	86	540
	3P						75				770
	4P						100				1,460
NF50-CN	2P	10.15.20.30.40.50.	5/2.5	2.5/1.3	2.5/1.3	1.5/0.8	50	130	68	86	790
	3P						75				830
	4P						100				1,740
NF100-CN	2P	10.15.20.30.40.50.	10/5	7.5/3.8	7.5/3.8	5/2.5	50	130	68	86	940
		60.75.100.					1,140				
	3P	10.15.20.30.40.50.					75				1,040
		60.75.100.					1,450				
	4P	10.15.20.30.40.50.					100				1,830
		60.75.100.					2,630				
NF100-SN	2P	10.15.20.30.40.50.	25/13	15/7.5	10/5	7.5/3.8	50	130	68	86	1,030
		60.75.100.					1,170				
	3P	10.15.20.30.40.50.					75				1,180
		60.75.100.					1,490				
	4P	10.15.20.30.40.50.					100				2,060
		60.75.100.					2,860				
NF125-SN	2P	10.15.20.30.40.50.	30/15	22/11	15/7.5	7.5/3.8	60	155	68	90	1,210
		60.75.100.125.					1,310				
	3P	10.15.20.30.40.50.					90				1,670
		60.75.100.125.					1,710				
	4P	10.15.20.30.40.50.					120				2,850
		60.75.100.125.					3,160				
NF125-HN	2P	10.15.20.30.40.50.	50/25	30/15	25/13	15/7.5	60	155	68	90	1,880
		60.75.100.125.					2,020				
	3P	10.15.20.30.40.50.					90				2,030
		60.75.100.125.					2,140				
	4P	10.15.20.30.40.50.					120				3,550
		60.75.100.125.					3,950				
NF250-CN	2P	125.150.175.200.225.	30/15	22/11	15/7.5	7.5/3.8	105	165	68	92	2,900
		250.					3,330				
	3P	125.150.175.200.225.					105				3,400
		250.					3,530				
	4P	125.150.175.200.225.					140				5,360
		250.					5,610				
NF250-SN	2P	125.150.175.200.225.	50/25	30/15	25/13	15/7.5	105	165	68	92	4,130
		250.					4,700				
	3P	125.150.175.200.225.					105				4,580
		250.					4,900				
	4P	125.150.175.200.225.					140				5,580
		250.					5,720				